

Morphological operations on binary images.

In this exercise you practice to use the basic morphological operations erosion and dilation on binary images.

Erosion is written as $b = (b1 \ominus se)$, where $b1$ is the original binary image, se is the *structure element*, and b is the eroded image. The symbol \ominus is used for the erosion operation. Erosion is implemented as a *Min-filter* (i.e. the result is the minimum of the image pixels pointed out by the structure element).

Dilation is written as $b = (b1 \oplus se)$, where $b1$ is the original binary image, se is the structure element, and b is the dilated image. The symbol \oplus is used for the dilation operation. Dilation is implemented as a *Max-filter* (i.e. the result is the maximum of the image pixels pointed out by the structure element).

1. Erosion

Create a binary image $b1$, and two structure elements $se1$ and $se2$.

Erode the binary image $b1$, using the two structuring elements $se1$ and $se2$.

```
% create the binary image b1
b1=zeros(16,16); %white object on a black background
b1(7:9,4:12)=ones(3,9);
subplot(2,2,1); imshow(b1); axis on %display
% create the structuring elements
se1=ones(1,3); % 1 x 3
se2=ones(3,1); % 3 x 1
se1 %print them on screen
se2 %
% erode the image b1
e1b1=imerode(b1,se1); %by se1
e2b1=imerode(b1,se2); %by se2
subplot(2,2,2); imshow(e1b1); axis on;
subplot(2,2,4); imshow(e2b1); axis on;
```

Erode $b1$ by using the 2D structure element $se=ones(3,3)$. Compare this result to the previous results using $se1$ and $se2$ ($se=se1 \oplus se2$).

What is the general result of erosion?

Do one of the above erosions yourself on a paper. Check against MATLAB result!

You want the object to disappear when doing the erosion. How should the structuring element look like for doing this? Test your idea in MATLAB.

2. Dilation

Create a binary image $b2$.

Dilate the binary image $b2$, using the two structuring elements $se1$ and $se2$.

```
% create the binary image b2
b2=zeros(16,16); %black background
b2(4:12, 6:10)=ones(9,5); %object
b2(6:10, 7:9)=zeros(5,3); %hole
subplot(2,2,1); imshow(b2); axis on;
% dilate the image b2
d1b2=imdilate(b2,se1); %by se1
d2b2=imdilate(b2,se2); %by se2
subplot(2,2,2); imshow(d1b2); axis on;
subplot(2,2,4); imshow(d2b2); axis on;
```

Dilate $b2$ by using the 2D structure element $se=ones(3,3)$. Compare this result to the previous results using $se1$ and $se2$ ($se=se1 \oplus se2$).

What is the general result of a dilation?

Do one of the above dilations yourself on a paper. Check against MATLAB result!

You want to "fill" the hole in the object when doing the dilation. How should the structuring element look like to do this? Test your idea in MATLAB.

3. Boundary extraction using erosion and dilation

Create a binary image b_3 . Extract the "inner boundary ib " of the object by using $ib = b_3 / (b_3 \ominus se)$.

Where the symbol $/$ means set difference, that is "everything in b_3 but not in $(b_3 \ominus se)$ ".

In the code below the symbols $\&$ and \sim means logical AND respectively logical complement (NOT).

```
b3=zeros(32,32);
b3(6:26,12:20)=ones(21,9);
subplot(2,2,1); imshow(b3); axis on;
```

```
se=ones(3,3); % 3 x 3 structuring element
se %print it on screen
```

```
b3e=imerode(b3,se);
subplot(2,2,3); imshow(b3e); axis on
ib=b3 & ~b3e; % extract the "inner boundary", can be interpreted as the difference  $b_3 - b_{3e}$ 
subplot(2,2,2); imshow(ib); axis on;
```

Now, extract the "outer boundary ob " of the object, by using $ob = (b_3 \oplus se) / b_3$ (first dilate "then take the difference").

Display the original, the dilated and the outer boundary image.

4. Closing and Opening operations for noise reduction

Reduce "noise" in the binary image b_4 , i.e. take away small objects in the background and "fill" small holes in the object. The object size should not be altered!

```
%Create the image b4
b4=zeros(32,32);
b4(6:26,12:20)=ones(21,9); %object
b4(18,15:16)=zeros(1,2); %small holes (noise)
b4(7:9,18)=zeros(3,1);
b4(27,27)=ones(1,1); %small objects (noise)
b4( 10:12,3)=ones(3,1);
subplot(2,2,1); imshow(b4); axis on; %display image
```

Use the Opening operation: $(b \ominus se) \oplus se$ and the Closing operation: $(b \oplus se) \ominus se$ to apply "noise reduction to the binary image b_4 . Display the original image and the result images from the opening respectively the closing operation.

Motivate the size of the structuring element se .

Why are you doing imerode and imdilate on the dilated respectively the eroded image for the closing and the opening operation?

5. Extract objects with a special property (here: big objects)

Extract the big object from the binary image b_5 .

Display the original image and your result image.

Hint:

First, use erosion to "take away" only the small objects (eb_5 is the result image of this operation).

Second, recover the big object by using iteratively $k_{i+1} = (k_i \oplus \text{ones}(3,3)) \& b_5$ until no changes, where $k_0 = eb_5$.

```

% Create the image b5.
b5=zeros(32,32);

b5(10:24,18:24)=ones(15,7); % the big object
b5(8:9,18)=ones(2,1); % that should
b5(24,16:17)=ones(1,2); be extracted

b5(4:5,5)=ones(2,1); % small object
b5(28,16:17)=ones(1,2); % small object

subplot(3,3,1); imshow(b5); axis on; % display image

% delete small objects < se
se=ones(3,3);
eb5=imerode(b5,se);
subplot(3,3,2); imshow(eb5); axis on;
% recover the big object iteratively
k1=imdilate(eb5,se) & b5;
subplot(3,3,4); imshow(k1); axis on;
k2=imdilate(k1,se) & b5;
subplot(3,3,5); imshow(k2); axis on;

```

Complete the above code until the big object is fully recovered.

Explain in words the effect of using the operation `imdilate` and the logical operation `AND` in the iteratively recovering of the big object from the eroded original image.

If you have time:

Load the character `E` and extract its boundary using morphological operations.